

## AXIS F2135-RE Fisheye Sensor

Discreet fisheye sensor with 1080p

AXIS F2135-RE offers 1080p at 60 fps or 720p at 180 fps with AXIS F9111, an excellent 185° field of view, and good low-light performance in color. It uses cables (up to 30 m/ 98 ft) from Axis with SMA-FAKRA connectors to withstand vibrations and ensure a ruggedized installation. Based on a divided network camera concept, it offers discreet installation and only a small sensor visible externally. Reliable under rough conditions, this ruggedized fisheye sensor unit can withstand temperatures as low as -40 °C and as high as 70 °C intermittently (-40 °F to 158 °F).

- > **Up to 60 fps at 1080p**
- > **Up to 180 fps at 720p**
- > **Excellent 185° field of view**
- > **Rugged sensor unit**
- > **IP66/IP67/IP6K9K-rated**



## AXIS F2135-RE Fisheye Sensor

Camera		Storage conditions
Image sensor	1/2.8" progressive scan RGB CMOS	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
Lens	1.98 mm, F2.0 <b>For 1080p:</b> Horizontal field of view: 185° Vertical field of view: 97° <b>For 720p:</b> Horizontal field of view: 120° Vertical field of view: 62° M12 mount, fixed iris	Approvals EMC CISPR 24, EN 55032 Class A, EN 55035, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), VCCI Class A, RCM AS/NZS CISPR 32 Class A, KC KN32 Class A, KC KN35, EAC, ECE R10 rev.05 (E-mark) Safety IEC/EN/UL 62368-1, CAN/CSA C22.2 No. 62368-1, IEC/EN/UL 60950-22, CAN/CSA-C22.2 No. 60950-22, UN ECE R118 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-64, IEC 60068-2-78, IEC TR 60721-4-5 Class 5M3 (vibration, shock), IEC/EN 60529 IP66/IP67/IP69, IEC/EN 61373 Category 1 Class B, NEMA 250 Type 4X, NEMA TS 2 (2.2.7-2.2.9), ISO 21207 (Method B) ISO 20653 IP6K9K
Minimum illumination	Color: 0.1 lux	Dimensions 46 mm (1.8 in) ø 29.8 mm (1.2 in)
Day and night	Fixed IR-cut filter	Weight 50 g (0.1 lb)
Shutter speed	<b>With AXIS F9111:</b> 1080p, 25/30 fps: 1/20000 s to 1.5 s 1080p, 50/60 fps: 1/27000 s to 1 s HDTV 720p, 175/180 fps: 1/32500 s to 0.5 s <b>With AXIS F9104-B, F9114 and F9114-B:</b> 1080p, 25/30 fps: 1/20000 s to 1.5 s HDTV 720p, 50/60 fps: 1/32500 s to 0.5 s	Required hardware AXIS TU6004 CL2 Cable SMA-FAKRA, AXIS TU6005 Plenum Cable SMA-FAKRA, AXIS F91 Main Unit
General		Included accessories Installation guide
Casing	IP67-, IP69-, IP6K9K-, NEMA 4X-rated Aluminum Color: black NCS S 9000-N	Optional accessories For more accessories, see <a href="http://axis.com">axis.com</a>
Sustainability	PVC free	Warranty 5-year warranty, see <a href="http://axis.com/warranty">axis.com/warranty</a>
Power	Typical 1 W, max 1.7 W	
Connectors	SMA connector	
Operating conditions	-40°C to 60 °C (-40°F to 140 °F) Maximum temperature according to NEMA TS 2 (2.2.7): 74 °C (165 °F) Start-up temperature: -40 °C (-40°F) Humidity 10–100% RH (condensing)	Environmental responsibility: <a href="http://axis.com/environmental-responsibility">axis.com/environmental-responsibility</a>